

SECTION 1: IDENTIFICATION**Product Identifier****Product Form:** Mixture**Product Name:** IMPERSOL™**Product Code:** F02467**Intended Use of the Product**

Acrylic base coat. For professional use only

Name, Address, and Telephone of the Responsible Party**Manufacturer**

Bitec, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

F-501-354-3019

www.bi-tec.com**Emergency Telephone Number****Emergency number** : 1-800-535-8597**SECTION 2: HAZARDS IDENTIFICATION****Classification of the Substance or Mixture****Classification (GHS-US)**

Skin Irrit. 2 H315

Eye Irrit. 2A H319

STOT SE 3 H335

STOT RE 2 H373

Label Elements**GHS-US Labeling****Hazard Pictograms (GHS-US)** :

GHS07



GHS08

Signal Word (GHS-US) : Warning**Hazard Statements (GHS-US)** : H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)**Precautionary Statements (GHS-US)** : P261 - Avoid breathing mist, spray, vapors
P264 - Wash hands, forearms, and exposed areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective gloves
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER/doctor/physician if you feel unwell
P321 - Specific treatment (see Section 4)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P501 - Dispose of contents/container according to local, regional, national, and international regulations

Other Hazards

Other Hazards Not Contributing to the Classification: Not available

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Acrylic Polymer Solution		20 - 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Ethylene glycol	(CAS No) 107-21-1	1 - 5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
Cellulose, 2-hydroxyethyl ether	(CAS No) 9004-62-0	0.1 - 1	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Pentapotassium triphosphate	(CAS No) 13845-36-8	0.1 - 1	Comb. Dust Acute Tox. 4 (Oral), H302
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	(CAS No) 25265-77-4	0.1 - 1	Aquatic Acute 3, H402

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion: Rinse mouth. Do NOT induce vomiting.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritation to eyes, skin and respiratory tract. Causes damage to organs (kidneys) (Oral).

Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion may cause nausea, vomiting and diarrhea.

Chronic Symptoms: Causes damage to organs through prolonged or repeated exposure.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide, dry chemical, foam, water spray, fog.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Not available

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Oxides of aluminum. Oxides of titanium.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Handle in accordance with good industrial hygiene and safety practice.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Absorb and/or contain spill with inert material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash hands and forearms thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Incompatible Materials: None known.

Storage Temperature: > 0 °C (32°F)

Specific End Use(s) Acrylic base coat

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Ethylene glycol (107-21-1)		
Mexico	OEL Ceiling (mg/m ³)	100 mg/m ³
USA ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³
Alberta	OEL Ceiling (mg/m ³)	100 mg/m ³
British Columbia	OEL Ceiling (mg/m ³)	100 mg/m ³
British Columbia	OEL Ceiling (ppm)	50 ppm
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³
Manitoba	OEL Ceiling (mg/m ³)	100 mg/m ³
New Brunswick	OEL Ceiling (mg/m ³)	100 mg/m ³
Newfoundland & Labrador	OEL Ceiling (mg/m ³)	100 mg/m ³
Nova Scotia	OEL Ceiling (mg/m ³)	100 mg/m ³
Nunavut	OEL Ceiling (mg/m ³)	127 mg/m ³
Nunavut	OEL Ceiling (ppm)	50 ppm
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL Ceiling (mg/m ³)	127 mg/m ³
Northwest Territories	OEL Ceiling (ppm)	50 ppm
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL Ceiling (mg/m ³)	100 mg/m ³
Prince Edward Island	OEL Ceiling (mg/m ³)	100 mg/m ³

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Québec	PLAFOND (mg/m ³)	127 mg/m ³
Québec	PLAFOND (ppm)	50 ppm
Saskatchewan	OEL Ceiling (mg/m ³)	100 mg/m ³
Yukon	OEL STEL (mg/m ³)	325 mg/m ³
Yukon	OEL STEL (ppm)	125 ppm
Yukon	OEL TWA (mg/m ³)	250 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm
Titanium dioxide (13463-67-7)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective goggles.



Materials for Protective Clothing: Not available

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White
Odor	: Slight
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing Point	: Not available
Boiling Point	: 100 °C (212°F)
Flash Point	: Not available
Auto-ignition Temperature	: < 204 (400°F)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: > 1 mm Hg
Relative Vapor Density at 20 °C	: < 1
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Soluble in water
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

- Reactivity:** Hazardous reactions will not occur under normal conditions.
- Chemical Stability:** Stable at standard temperature and pressure.
- Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures.
- Incompatible Materials:** None known.
- Hazardous Decomposition Products:** When heated, material emits irritating fumes.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

- Acute Toxicity:** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Causes skin irritation.
- Serious Eye Damage/Irritation:** Causes serious eye irritation.
- Respiratory or Skin Sensitization:** Not classified
- Germ Cell Mutagenicity:** Not classified
- Teratogenicity:** Not available
- Carcinogenicity:** Not classified
- Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
- Reproductive Toxicity:** Not classified
- Specific Target Organ Toxicity (Single Exposure):** May cause respiratory irritation.
- Aspiration Hazard:** Not classified
- Symptoms/Injuries After Inhalation:** May cause respiratory irritation. May cause drowsiness or dizziness.
- Symptoms/Injuries After Skin Contact:** Causes skin irritation.
- Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.
- Symptoms/Injuries After Ingestion:** Ingestion may cause nausea, vomiting and diarrhea.
- Chronic Symptoms:** Causes damage to organs through prolonged or repeated exposure.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Aluminum hydroxide (Al(OH)3) (21645-51-2)	
LD50 Oral Rat	> 5000 mg/kg
Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylene glycol (107-21-1)	
LD50 Oral Rat	4000 mg/kg
LD50 Dermal Rabbit	3500 mg/kg
Pentapotassium triphosphate (13845-36-8)	
LD50 Oral Rat	2000 mg/kg
Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
LD50 Oral Rat	3200 mg/kg
LD50 Dermal Rat	> 15200 mg/kg
Titanium dioxide (13463-67-7)	
IARC Group	2B

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified

Ethylene glycol (107-21-1)	
LC50 Fish 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
LC50 Fish 1	30 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

Persistence and Degradability

IMPERSOL™	
Persistence and Degradability	Not established.

Bioaccumulative Potential

IMPERSOL™	
Bioaccumulative Potential	Not established.

Ethylene glycol (107-21-1)	
Log Pow	-1.93

2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
Log Pow	3.47 (at 25 °C)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

- 14.1 In Accordance with DOT** Not regulated for transport
- 14.2 In Accordance with IMDG** Not regulated for transport
- 14.3 In Accordance with IATA** Not regulated for transport
- 14.4 In Accordance with TDG** Not regulated for transport

SECTION 15: REGULATORY INFORMATION


US Federal Regulations

Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cellulose, 2-hydroxyethyl ether (9004-62-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Ethylene glycol (107-21-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
SARA Section 313 - Emission Reporting	1.0 %
Pentapotassium triphosphate (13845-36-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Titanium dioxide (13463-67-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Ethylene glycol (107-21-1)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Titanium dioxide (13463-67-7)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Canadian Regulations	
IMPERSOL™	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Water (7732-18-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Cellulose, 2-hydroxyethyl ether (9004-62-0)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Ethylene glycol (107-21-1)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Pentapotassium triphosphate (13845-36-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Titanium dioxide (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

IMPERSOL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
2,2,4-Trimethylpentane-1,3-diol monoisobutyrate (25265-77-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 05/07/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Bitec, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

F-501-354-3019

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2012 & WHMIS