

SECTION 1: IDENTIFICATION**Product Identifier****Product Form:** Mixture**Product Name:** PMA-186™**Product Code:** F02339**Intended Use of the Product**

Cold process, asphalt modified, interply adhesive. For professional use only.

Name, Address, and Telephone of the Responsible Party**Manufacturer**

Bitec, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

F-501-354-3019

www.bi-tec.com**Emergency Telephone Number****Emergency number** : 1-800-535-8597**SECTION 2: HAZARDS IDENTIFICATION****Classification of the Substance or Mixture****Classification (GHS-US)**

Flam. Liq. 3 H226

Eye Irrit. 2A H319

Muta. 1B H340

Carc. 1A H350

STOT RE 2 H373

Asp. Tox. 1 H304

Aquatic Acute 1 H400

Aquatic Chronic 2 H411

Label Elements**GHS-US Labeling****Hazard Pictograms (GHS-US)** :

GHS02



GHS07



GHS08



GHS09

Signal Word (GHS-US) :

: Danger

Hazard Statements (GHS-US) :: H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H340 - May cause genetic defects
H350 - May cause cancer (Inhalation)
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects**Precautionary Statements (GHS-US)** :: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe mist/vapors/spray
P264 - Wash hands, forearms, and exposed areas thoroughly after handling
P273 - Avoid release to the environment

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear eye protection, protective gloves, protective clothing
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice and attention if you feel unwell
P331 - If swallowed, do NOT induce vomiting
P337+P313 - If eye irritation persists: Get medical advice/attention
P370+P378 - In case of fire: Use appropriate media to extinguish
P391 - Collect spillage
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container according to local, regional, national, and international regulations

Other Hazards

Other Hazards Not Contributing to the Classification: Contains a small amount of hydrogen sulfide. Hydrogen sulfide is a fatal and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of hydrogen sulfide. Hydrogen sulfide is also an asphyxiant.

Unknown Acute Toxicity (GHS-US)

<2% of the mixture consists of ingredients of unknown acute toxicity.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Asphalt	(CAS No) 8052-42-4	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Carc. 2, H351
Stoddard solvent	(CAS No) 8052-41-3	10 - 30	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Hydrogen sulfide	(CAS No) 7783-06-4	1 - 5	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 Eye Irrit. 2A, H319 STOT SE 1, H370 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 - 4	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Attapulgit	(CAS No) 12174-11-7	1 - 4	Carc. 2, H351
Cumene	(CAS No) 98-82-8	1 - 2	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 STOT SE 1, H370 STOT RE 1, H372 Asp. Tox. 1, H304

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

			Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Solvent naphtha, petroleum, light aromatic	(CAS No) 64742-95-6	1 - 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	1 - 2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1 - 2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Cellulose	(CAS No) 9004-34-6	0.5 - 1.5	Comb. Dust
Quartz	(CAS No) 14808-60-7	0.1 - 1	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372
Alcohols, C9-11-iso-, C10-rich	(CAS No) 68526-85-2	0.01	Aquatic Acute 1, H400

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. If exposed or concerned: Get medical advice/attention.

Skin Contact: Remove contaminated clothing. Rinse affected area with water for at least 5 minutes.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation.

Inhalation: May cause cancer by inhalation.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye irritation.

Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause genetic defects. May cause cancer.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable Extinguishing Media: Do not use water jet. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Not available

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur and/or nitrogen. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures. Corrosive vapors.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Handle in accordance with good industrial hygiene and safety practice. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. Use appropriate personal protection equipment (PPE).

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Collect spillage. Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s) Adhesive

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Asphalt (8052-42-4)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	5 mg/m ³ (Petroleum; Bitumen)
British Columbia	OEL TWA (mg/m ³)	0.5 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.5 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³ (petroleum fumes)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.5 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.5 mg/m ³
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³ (Petroleum fumes)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (Petroleum fumes)
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³ (Petroleum fumes)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (Petroleum fumes)
Ontario	OEL TWA (mg/m ³)	0.5 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	0.5 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	1.5 mg/m ³ (fumes)
Saskatchewan	OEL TWA (mg/m ³)	0.5 mg/m ³
Yukon	OEL STEL (mg/m ³)	10 mg/m ³
Yukon	OEL TWA (mg/m ³)	5 mg/m ³
Hydrogen sulfide (7783-06-4)		
Mexico	OEL TWA (mg/m ³)	14 mg/m ³
Mexico	OEL TWA (ppm)	10 ppm
Mexico	OEL STEL (mg/m ³)	21 mg/m ³
Mexico	OEL STEL (ppm)	15 ppm
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	15 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (ppm)	10 ppm
USA IDLH	US IDLH (ppm)	100 ppm
Alberta	OEL Ceiling (mg/m ³)	21 mg/m ³
Alberta	OEL Ceiling (ppm)	15 ppm
Alberta	OEL TWA (mg/m ³)	14 mg/m ³
Alberta	OEL TWA (ppm)	10 ppm
British Columbia	OEL Ceiling (ppm)	10 ppm
Manitoba	OEL STEL (ppm)	5 ppm
Manitoba	OEL TWA (ppm)	1 ppm
New Brunswick	OEL STEL (mg/m ³)	21 mg/m ³
New Brunswick	OEL STEL (ppm)	15 ppm
New Brunswick	OEL TWA (mg/m ³)	14 mg/m ³
New Brunswick	OEL TWA (ppm)	10 ppm
Newfoundland & Labrador	OEL STEL (ppm)	5 ppm
Newfoundland & Labrador	OEL TWA (ppm)	1 ppm
Nova Scotia	OEL STEL (ppm)	5 ppm
Nova Scotia	OEL TWA (ppm)	1 ppm
Nunavut	OEL Ceiling (mg/m ³)	28 mg/m ³
Nunavut	OEL Ceiling (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	21 mg/m ³
Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (mg/m ³)	14 mg/m ³
Nunavut	OEL TWA (ppm)	10 ppm
Northwest Territories	OEL Ceiling (mg/m ³)	28 mg/m ³
Northwest Territories	OEL Ceiling (ppm)	20 ppm

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Northwest Territories	OEL STEL (mg/m ³)	21 mg/m ³
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (mg/m ³)	14 mg/m ³
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	5 ppm
Prince Edward Island	OEL TWA (ppm)	1 ppm
Québec	VECD (mg/m ³)	21 mg/m ³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m ³)	14 mg/m ³
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m ³)	27 mg/m ³
Yukon	OEL STEL (ppm)	15 ppm
Yukon	OEL TWA (mg/m ³)	15 mg/m ³
Yukon	OEL TWA (ppm)	10 ppm
Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Stoddard solvent (8052-41-3)		
Mexico	OEL TWA (mg/m ³)	523 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	1050 mg/m ³
Mexico	OEL STEL (ppm)	200 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
USA IDLH	US IDLH (mg/m ³)	20000 mg/m ³
Alberta	OEL TWA (mg/m ³)	572 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (mg/m ³)	580 mg/m ³
British Columbia	OEL TWA (mg/m ³)	290 mg/m ³
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL TWA (mg/m ³)	525 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m ³)	720 mg/m ³
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (mg/m ³)	575 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	720 mg/m ³
Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (mg/m ³)	575 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (mg/m ³)	525 mg/m ³ (140°C Flash aliphatic solvent)
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VEMP (mg/m ³)	525 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	720 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	575 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm
1,3,5-Trimethylbenzene (108-67-8)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)		
Mexico	OEL TWA (mg/m ³)	435 mg/m ³
Mexico	OEL TWA (ppm)	100 ppm
Mexico	OEL STEL (mg/m ³)	655 mg/m ³
Mexico	OEL STEL (ppm)	150 ppm
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Alberta	OEL STEL (mg/m ³)	651 mg/m ³
Alberta	OEL STEL (ppm)	150 ppm
Alberta	OEL TWA (mg/m ³)	434 mg/m ³
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (ppm)	150 ppm
British Columbia	OEL TWA (ppm)	100 ppm
Manitoba	OEL STEL (ppm)	150 ppm
Manitoba	OEL TWA (ppm)	100 ppm
New Brunswick	OEL STEL (mg/m ³)	651 mg/m ³
New Brunswick	OEL STEL (ppm)	150 ppm
New Brunswick	OEL TWA (mg/m ³)	434 mg/m ³
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	150 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL STEL (ppm)	150 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (mg/m ³)	652 mg/m ³
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (mg/m ³)	434 mg/m ³
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (mg/m ³)	652 mg/m ³
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (mg/m ³)	434 mg/m ³
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	150 ppm
Ontario	OEL TWA (ppm)	100 ppm
Prince Edward Island	OEL STEL (ppm)	150 ppm
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VECD (mg/m ³)	651 mg/m ³
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m ³)	434 mg/m ³
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m ³)	650 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Yukon	OEL TWA (mg/m ³)	435 mg/m ³
Yukon	OEL TWA (ppm)	100 ppm
Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.3 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³
Québec	VEMP (mg/m ³)	0.1 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL TWA (mg/m ³)	300 particle/mL
Kaolin (1332-58-7)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	2 mg/m ³
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Québec	VEMP (mg/m ³)	5 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	4 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Attapulgite (12174-11-7)		
Québec	VEMP (mg/m ³)	1 fibers/cm ³
Cellulose (9004-34-6)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Limestone (1317-65-3)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Cumene (98-82-8)		
Mexico	OEL TWA (mg/m ³)	245 mg/m ³
Mexico	OEL TWA (ppm)	50 ppm
Mexico	OEL STEL (mg/m ³)	365 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	245 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	245 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
USA IDLH	US IDLH (ppm)	900 ppm (10% LEL)
Alberta	OEL TWA (mg/m ³)	246 mg/m ³
Alberta	OEL TWA (ppm)	50 ppm
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	25 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL TWA (mg/m ³)	246 mg/m ³
New Brunswick	OEL TWA (ppm)	50 ppm

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Newfoundland & Labrador	OEL TWA (ppm)	50 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (mg/m ³)	370 mg/m ³
Nunavut	OEL STEL (ppm)	75 ppm
Nunavut	OEL TWA (mg/m ³)	245 mg/m ³
Nunavut	OEL TWA (ppm)	50 ppm
Northwest Territories	OEL STEL (mg/m ³)	370 mg/m ³
Northwest Territories	OEL STEL (ppm)	75 ppm
Northwest Territories	OEL TWA (mg/m ³)	245 mg/m ³
Northwest Territories	OEL TWA (ppm)	50 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VEMP (mg/m ³)	246 mg/m ³
Québec	VEMP (ppm)	50 ppm
Saskatchewan	OEL STEL (ppm)	74 ppm
Saskatchewan	OEL TWA (ppm)	50 ppm
Yukon	OEL STEL (mg/m ³)	365 mg/m ³
Yukon	OEL STEL (ppm)	75 ppm
Yukon	OEL TWA (mg/m ³)	245 mg/m ³
Yukon	OEL TWA (ppm)	50 ppm
Magnesium carbonate (546-93-0)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Take precautionary measures against static discharges. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapours may be released.

Personal Protective Equipment: On heating: wear respiratory equipment. Protective clothing. Protective goggles. Gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Not available

Respiratory Protection: When manufacturing or handling product in large quantities and vapors or mists may be generated, maintain airborne concentrations below recommended limits. Workplace risk assessments should be completed before specifying and implementing respirator usage. NIOSH approved respirators for protection should be used if respirators are found to be necessary.

Other Information: When using, do not eat, drink or smoke.

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Viscous, Black
Odor	: Petroleum distillate
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 149 - 199 °C (300.2-390.2°F)
Flash Point	: 41 °C (105.8°F) TCC
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 0.9
Solubility	: Insoluble
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). May release flammable gases. Contains a small amount of hydrogen sulfide. Hydrogen sulfide is a fatal, and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of hydrogen sulfide. Hydrogen sulfide is also an asphyxiant.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: May cause genetic defects.

___Teratogenicity: Not available

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause cancer by inhalation.

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause genetic defects. May cause cancer.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Asphalt (8052-42-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
Hydrogen sulfide (7783-06-4)	
LC50 Inhalation Rat (mg/l)	0.99 mg/l (Exposure time: 1 h)
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat (mg/l)	18 g/m ³ (Exposure time: 4 h)
Stoddard solvent (8052-41-3)	
LD50 Oral Rat	> 5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 mg/kg
1,3,5-Trimethylbenzene (108-67-8)	
LC50 Inhalation Rat (mg/l)	24 g/m ³ (Exposure time: 4 h)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	4300 mg/kg
LC50 Inhalation Rat (mg/l)	47635 mg/l/4h (Exposure time: 4 h)
LC50 Inhalation Rat (ppm)	6247 ppm/4h (species: Sprague-Dawley)
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat (ppm)	3400 ppm/4h
Cellulose (9004-34-6)	
LC50 Inhalation Rat (mg/l)	> 5800 mg/m ³ (Exposure time: 4 h)
Alcohols, C9-11-iso-, C10-rich (68526-85-2)	
LD50 Oral Rat	> 2648 mg/kg
LD50 Dermal Rabbit	> 3.16 mg/kg
LC50 Inhalation Rat (ppm)	> 95.3 ppm
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
LD50 Oral Rat	> 5000 mg/kg
Cumene (98-82-8)	
LD50 Oral Rat	2260 mg/kg
LD50 Dermal Rabbit	10000 mg/kg
LC50 Inhalation Rat (mg/l)	20 - 40 mg/l (Exposure time: 6 h)
Asphalt (8052-42-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Twelfth Report - Items under consideration.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC Group	3
Quartz (14808-60-7)	
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.
Attapulgate (12174-11-7)	
IARC Group	2B, 3

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Styrene-butadiene copolymer (9003-55-8)	
IARC Group	3
Cumene (98-82-8)	
IARC Group	2B
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Hydrogen sulfide (7783-06-4)	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC 50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 Fish 1	7.19 (7.19 - 8.28) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Stoddard solvent (8052-41-3)	
LC50 Fish 1	0.42 mg/l

1,3,5-Trimethylbenzene (108-67-8)	
LC50 Fish 1	3.48 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	2.661 (2.661 - 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 Fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Alcohols, C9-11-iso-, C10-rich (68526-85-2)	
LC50 Fish 1	3 mg/l
LC50 other aquatic organisms 1	2.4 mg/l Algae
EC50 Daphnia 1	4 µg/l

Cumene (98-82-8)	
LC50 Fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

Persistence and Degradability

PMA-186™	
Persistence and Degradability	Not established. May cause long-term adverse effects in the environment.

Bioaccumulative Potential

PMA-186™	
Bioaccumulative Potential	Not established.

Asphalt (8052-42-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	> 6

Hydrogen sulfide (7783-06-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	0.45 (at 25 °C)

Benzene, 1,2,4-trimethyl- (95-63-6)	
Log Pow	3.63

Stoddard solvent (8052-41-3)	
Log Pow	3.16 (Octanol/water partition coefficient 3.16/7.06)

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 (0.6 - 15)
Log Pow	2.77 - 3.15
Cumene (98-82-8)	
BCF fish 1	35.5
Log Pow	3.55 (at 23 °C)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology – Waste Materials: Hazardous waste due to toxicity. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Not regulated

Hazard Class :

Identification Number : UN1999

Label Codes :

Packing Group :

ERG Number :

14.2 In Accordance with IMDG

Proper Shipping Name : TARS, LIQUID

Hazard Class : 3

Identification Number : UN1999

Packing Group : III

Label Codes : 3

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

MFAG Number : 130



14.3 In Accordance with IATA

Proper Shipping Name : TARS, LIQUID

Packing Group : III

Identification Number : UN1999

Hazard Class : 3

Label Codes : 3

ERG Code (IATA) : 3L



14.4 In Accordance with TDG

Proper Shipping Name : Not regulated

Packing Group :

Hazard Class :

Identification Number :

Label Codes :

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Asphalt (8052-42-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Hydrogen sulfide (7783-06-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on SARA Section 302 (Specific toxic chemical listings)
Listed on SARA Section 313 (Specific toxic chemical listings)

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 %
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %
Stoddard solvent (8052-41-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
1,3,5-Trimethylbenzene (108-67-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
1-Propanamine, 3-(isodecyloxy)-, acetate (28701-67-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb
SARA Section 313 - Emission Reporting	1.0 %
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Kaolin (1332-58-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Styrene-butadiene copolymer (9003-55-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cellulose (9004-34-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Alcohols, C9-11-iso-, C10-rich (68526-85-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cumene (98-82-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 313 - Emission Reporting	1.0 %
Magnesium carbonate (546-93-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Attapulgate (12174-11-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

PMA-186

Safety Data Sheet



according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cumene (98-82-8)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Asphalt (8052-42-4)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Hydrogen sulfide (7783-06-4)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Benzene, 1,2,4-trimethyl- (95-63-6)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Stoddard solvent (8052-41-3)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
1,3,5-Trimethylbenzene (108-67-8)	
RTK - U.S. - Massachusetts - Right To Know List	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Quartz (14808-60-7)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Kaolin (1332-58-7)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Cellulose (9004-34-6)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Limestone (1317-65-3)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Cumene (98-82-8)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List RTK - U.S. - Pennsylvania - RTK (Right to Know) List	
Magnesium carbonate (546-93-0)	
RTK - U.S. - Massachusetts - Right To Know List RTK - U.S. - New Jersey - Right to Know Hazardous Substance List	
Canadian Regulations	
PMA-186™	

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
 	
Asphalt (8052-42-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Hydrogen sulfide (7783-06-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Stoddard solvent (8052-41-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
1,3,5-Trimethylbenzene (108-67-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 3 - Combustible Liquid
1-Propanamine, 3-(isodecyloxy)-, acetate (28701-67-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Kaolin (1332-58-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Styrene-butadiene copolymer (9003-55-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

PMA-186

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Cellulose (9004-34-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Alcohols, C9-11-iso-, C10-rich (68526-85-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Aluminum hydroxide (Al(OH)3) (21645-51-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Limestone (1317-65-3)	
Listed on Non-Domestic Substances List (NDSL)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Cumene (98-82-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Magnesium carbonate (546-93-0)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 01/01/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Bitec, Inc.
#2 Industrial Park Drive
Morrilton, AR 72110
T-800-535-8597
F-501-354-3019

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2012 & WHMIS