

Impersol™ Seam Tape

PRODUCT INFORMATION



OVERVIEW

Impersol Seam Tape is ideally suited for use with Impersol EB series of synthetic rubber coatings. They quickly wet-out and saturate the fiber structure of the fleece backing. These properties ensure a true monolithic membrane which remains intact even under thermal shock conditions.

WHEN QUALITY MATTERS™

USES

- Reinforces seams, cracks, and penetrations on various surfaces
- Single ply membranes
- Galvanized metal Roofing
- Concrete
- Modified bitumen

DIRECTIONS

Impersol Seam Tape is easy to apply. Simply line up the two adjoining areas to be sealed, with the release paper still attached, then start removing the release paper from the underside and placing the membrane close to the desired position. It can then be worked into all cracks and crevices using your fingers, a blunt awl, or plastic knife.

ADVANTAGES

Impersol Seam Tape provides good elongation and maintains its elasticity at extremely low temperatures. It cannot be stretched in the uncoiling direction, but can be easily stretched or formed across the web. It has no elastic memory and will not creep, allowing it to remain exactly where it is placed. When used with Impersol EB rubber coatings, they provide strong, flexible repairs.

Impersol Seam Tape is compatible with both solvent-based and water-based coatings.

Clean up: Tools and equipment can be easily cleaned with mineral spirits.

The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the products discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.

AVAILABLE SIZES

- 2" x 50' Roll
- 4" x 50' Roll



BITEC

P.O. Box 497

No. 2 Industrial Park Drive, Morrilton, Arkansas

72110 Phone 1-800-535-8597

Fax (501) 354-3019

www.bi-tec.com