

Impersol™ EB Flashing Compound

PRODUCT INFORMATION



OVERVIEW

Impersol EB Flashing Compound is a unique rubber compound that is extremely effective for sealing fasteners, laps and penetrations on various roof surfaces. It is a one-component product that has excellent adhesion to properly prepared substrates. Impersol EB Flashing Compound is thermally stable and resists cracking and peeling due to ozone and ultraviolet exposure. It is typically top-coated with Impersol EB All-In-One for maximum weather resistance. Impersol EB Flashing Compound has excellent physical properties and reduces costly re-applications.

WHEN QUALITY MATTERS™

TYPES OF APPLICATION

- Metal Buildings and Roofs
- Modified and BUR Roofs
- Urethane Foam Roofs
- Single Ply Roofs
- Concrete surfaces

SURFACE PREPARATION

The surface must be free of any dirt, moisture, oils, algae or other contaminants that may interfere with good adhesion. Carefully remove any loose material from surface with a wire brush or scraper. Grease and oil should also be removed with environmentally safe solvents or an appropriate detergent cleaner such as IMPERSOL Cleaner Degreaser. In most cases a high pressure water blast will be sufficient to prepare the surface.

APPLICATION TEMPERATURES

To obtain the best results, ambient temperatures of the air and the substrate should range between 40° - 100°F. Although lower temperatures can be used for brush applications, it is recommended that the product temperature be a minimum of 70°F when pumping the product.

APPLICATION METHODS

Impersol EB Flashing Compound can be brushed, rolled or pumped onto the surface. Apply heavy, uniform coat over fasteners, seams, etc. See BITEC application bulletins for additional information.

HANDLING & STORAGE

Impersol EB Flashing Compound vehicle is a blend of solvents considered combustible by the standards of the D.O.T. and O.S.H.A. Keep away from heat, open flame, or sparks. Use in a well ventilated area.

Notice: Impersol should be used and stored away from flames, in a well-ventilated atmosphere. Avoid prolonged breathing of vapors and prevent contact with eyes. Read all label information, SDS, and precautions before using. The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the products discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.

AVAILABLE SIZES

- 0.5 gallon
- 1.0 gallon
- 2.5 gallons
- 5.0 gallons

Technical Data	Flashing Compound
Viscosity	12,000 Cp
VOC	436 g/l
Solids (%/V)	53 +/- 1
Solids (%/wt)	60 +/- 1
Resin	Synthetic Rubber
Color	White
Reduction	None
Elongation	400 %



BITEC

P.O. Box 497

No. 2 Industrial Park Drive, Morrilton, Arkansas

72110 Phone 1-800-535-8597

Fax (501) 354-3019

www.bi-tec.com