

Impersol™ EB All-in-One

PRODUCT INFORMATION



OVERVIEW

Impersol EB All-in-One is a unique rubber coating that provides extremely effective protection. It is a one component product that has excellent adhesion to properly prepared surfaces.

Impersol EB All-in-One controls corrosion and rust bleed through, even after years of service. It is thermally stable and resists cracking and peeling due to weather extremes and ultraviolet exposure.

WHEN QUALITY MATTERS™

TYPES OF APPLICATION

- Metal Buildings and Roofs
- Modified and BUR Roofs
- Urethane Foam Roofs
- Single Ply Roofs
- Concrete surfaces

SURFACE PREPARATION

The surface must be free of any dirt, moisture, oils, algae or other contaminants that may interfere with good adhesion. Carefully remove any loose material from surface with a wire brush or scraper. Grease and oil should also be removed with environmentally safe solvents or an appropriate detergent cleaner such as Impersol Cleaner Degreaser. In most cases a high pressure water blast will be sufficient to prepare the surface.

APPLICATION TEMPERATURES

For best results, the temperature of the ambient air and the substrate should be within a range of 50°-100°F. For best spray application, the product should be at a minimum of 60°F. Lower temperatures can be utilized for brush applications.

APPLICATION METHODS

Impersol EB All-in-One can be applied by brush, spray or roller. Best results can be obtained with airless spray equipment. See BITEC Application Bulletins for additional information.

HANDLING & STORAGE

Impersol EB All-in-One vehicle is a blend of solvents considered combustible by the standards of the D.O.T. and O.S.H.A. Keep away from heat, open flame, or sparks. Use in a well ventilated area.

Notice: Impersol should be used and stored away from flames, in a well-ventilated atmosphere. Avoid prolonged breathing of vapors and prevent contact with eyes. Read all label information, SDS, and precautions before using. The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the products discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.

AVAILABLE SIZES

- 0.5 gallon
- 1.0 gallon
- 2.5 gallons
- 5.0 gallons

Wet Adhesion	(ASTM C794/D903)
Metal	Pass
SBS Mod. Bit	Pass
APP Mod. Bit	Pass
Smooth BUR	Pass
EPDM	Pass
TPO	Pass
Hypalon	Pass
SPUF (Foam)	Pass



BITEC
P.O. Box 497
No. 2 Industrial Park Drive, Morrilton, Arkansas
72110 Phone 1-800-535-8597
Fax (501) 354-3019
www.bi-tec.com