



KEE FLASHING COMPONENTS

Pre-molded KEE flashing components to be used in PVC and KEE roof systems

STRONGHOLD™

PRODUCT OVERVIEW & FEATURES

StrongHold KEE Flashing Components are manufactured from a specialized compound, utilizing DuPont® Elvaloy™ KEE (Ketone Ethylene Ester) compound as the principle polymer.

Pre molded KEE pipe flashings are injection molded and designed to accommodate cylindrical penetrations from 1-in up to 6-in in diameter.

Pre-molded universal inside/outside corner flashings are injection molded and designed to accommodate 90° inside or outside wall, curb and other rectangular penetration corners.

The use of pre-molded pipe and corner flashings significantly improves installation consistency and reduces field labor.

StrongHold also provides a 60-mil, non-reinforced KEE membrane to use in roofing applications where the pre-molded components do not accommodate the penetration.

StrongHold Reinforced stripping roll is used for tying in metal edges to the field surface and at end laps when using our KEE FB membranes.

APPLICATION

StrongHold KEE accessory components are formed and/or sealed in place using conventional hot air welding techniques. Consult the most current versions of Bitec's Guide Specifications for the Installation of KEE and PVC Roofing Systems and Installation Details for installation requirements, cautions and parameters.

PHYSICAL PROPERTIES

Pre-Molded Pipe Flashing	
Material	KEE
Thickness	0.55 in
Packaging	8 ea. per carton
Pre-Molded Inside/Outside Corner	
Material	KEE
Thickness	.080 in
Packaging	20 ea. per carton
Non-Reinforced Sheet	
Material	KEE
Thickness	.060 in
Packaging	4-ft x 24-ft rolls
Stripping Roll	
Material	KEE
Thickness	.036 in
Packaging	6" x 100" rolls

*Colors: KEE non-reinforced accessory components are stocked in our standard "off white."

